

| Item No.      |                      | HS-56541P   |   |  |
|---------------|----------------------|---|---|--|
| Image Sensor  | Mega Sensor          | 1/4" CMOS HI3518E+OV9712  | 1/3" CMOS HI3518E+AR0130                              | 1/3" CMOS HI3516C+IMX222   |
|               | Display(Main stream) | 1280*720, 1-25(30) frames   | 1280*960, 1-25(30) frames,                            | 1920*1080, 1-25(30) frames, 1280*720 1-25(30) frames,  |
|               | Display(Sub stream)  | 704*576, 1-6 frames<br>320*240, 1-25(30) frames                     | 720*576, 1-25(30) frames<br>640*480, 1-25(30) frames  | 704*576, 1-25(30) frames<br>640*480, 1-25(30) frames<br>640*352, 1-25(30) frames<br>320*240, 1-25(30) frames |
|               | Min. Illumination    | Color: 0.6lux@F1.2,<br>B&W:0.08lux@F1.2                             | Color: 0.01lux@F1.2,<br>B&W:0.01lux@F1.2              | Color: 0.01lux@F1.2,<br>B&W:0.001lux@F1.2  |
| Lens          | Lens                 | 3.6mm board lens  |   |  |
|               | Lens Type            | board lens  |   |  |
|               | Viewing Angle        | 92 degree   |   |  |
| IR            | IR Leds              | 36pcs   |   |  |
|               | IR Distance          | 30m   |   |  |
| Audio         | Microphone           | Two way Audio Optional  |   |  |
| Wifi          |                      | Optional  |   |  |
| Domin Name    | Server               | P2P(Danale software)/DDNS   |   |  |
| Video         | Image Compression    | H.264/MJPEG Dual Stream   |   |  |
|               | Bit Rate             | 32Kbps-16Mbps, Support CBR/VBR                                      |   |  |
|               | Resolution           | 1280*720, 704*576, 320*240  | 1280*1024, 1280*960,<br>1280*720, 720*576,<br>640*480 | 1920*1080, 1280*720,<br>704*576, 640*480, 640*352,<br>640*352  |
| Communication | Ethernet             | 1 to 10/100Mbps RJ-45   |   |  |
|               | Supported Protocol   | TCP/IP、UDP、RTP、RTSP、RTCP、HTTP、DNS、DDNS、DHCP、FTP、NTP、PPPOE、SMTP、UPNP |   |  |
|               | Onvif                | Standard V2.3   |   |  |
|               | Mobile Monitor       | Windows,Iphone, Android etc.  |   |  |
|               | Browser              | IE6.0 or up   |   |  |
|               | Record               | Manual, Auto(Cycling, Timing, Alarm, Motion Detect)                 |   |  |
|               | Alarm Doc.           | FTP, Email, Browser, Software                                       |   |  |
| Power         | Specification        | DC12V/POE   |   |  |
|               | Power consumption    | 2W(MAX)   |   |  |
| Environment   | Operate Temper       | -20℃ - +55℃   |   |  |
|               | Operating Humidity   | 0% - 90%  |   |  |