

Item No.		HS-5621IP		
Image Sensor	Mega Sensor	1/4" CMOS HI3518E+OV9712	1/3" CMOS HI3518E+AR0130	1/3" CMOS HI3516C+IMX222
	Display(Main stream)	1280*720, 1-25(30)frames	1280*960, 1-25(30) frames,	1920*1080, 1-25(30) frames, 1280*720 1-25(30) frames,
	Display(Sub stream)	704*576, 1-6 frames 320*240, 1-25(30) frames	720*576, 1-25(30) frames 640*480, 1-25(30) frames	704*576, 1-25(30) frames 640*480, 1-25(30) frames 640*352, 1-25(30) frames 320*240, 1-25(30) frames
	Min. Illumination	Color: 0.6lux@F1.2, B&W:0.08lux@F1.2	Color: 0.01lux@F1.2, B&W:0.01lux@F1.2	Color: 0.01lux@F1.2, B&W:0.001lux@F1.2
Lens	Lens	3.6mm board lens		
	Lens Type	board lens		
	Viewing Angle	92 degree		
IR	IR Leds	24pcs		
	IR Distance	20m		
Audio	Microphone	Two way Audio Optional		
Wifi		Optional		
Domin Name	Server	P2P(Danale software)/DDNS		
Video	Image Compression	H.264/MJPEG Dual Stream		
	Bit Rate	32Kbps-16Mbps, Support CBR/VBR		
	Resolution	1280*720, 704*576, 320*240	1280*1024, 1280*960, 1280*720, 720*576, 640*480	1920*1080, 1280*720, 704*576, 640*480, 640*352, 640*352
Communication	Ethernet	1 to 10/100Mbps RJ-45		
	Supported Protocol	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPoE, SMTP, UPNP		
	Onvif	Standard V2.3		
	Mobile Monitor	Windows, Iphone, Android etc.		
	Browser	IE6.0 or up		
	Record	Manual, Auto(Cycling, Timing, Alarm, Motion Detect)		
	Alarm Doc.	FTP, Email, Browser, Software		
Power	Specification	DC12V/POE		
	Power consumption	2W(MAX)		
Environment	Operate Temper	-20℃ - +55℃		
	Operating Humidity	0% - 90%		